Cost Summary

BSK-1: **€ 589 each**

Fire Protection Lithium-Ion Battery Case designed and built to the highest safety standards for the storage, transport and placement of lithium-ion batteries.
Including:

- *Pouches of extinguishing beads that melt and oxygen starve a potential battery fire.*
- *Cable gland to insert charging cable(s).*

Delivery: **Included to ROI.**

Lead-time: **1 – 2 weeks from receipt of order**

All figures are EUR and excluding VAT.
Quote valid for 30 days.
Standard Chemstore Terms & Conditions can be found at www.chemstore.ie/terms-and-conditions

Battery Case Specification

Features

- **Safe Storage and Transport:** Developed for the safe storage, transport, and placement of lithium-ion batteries.
- **Charging Capability:** Unique cable gland allows for charging batteries within the case.
- **Fire-Resistant Interior:** Equipped with fire-resistant fittings and PyroBubbles cushions for maximum safety.
- **Heat Resistance:** Ensures maximum outside temperature stays below 100°C, preventing emission of flames and splinters.
- **High Dielectric Safety:** Suitable for strong power tools and defective batteries.
- **Latest Technology:** Developed with the latest hazardous goods technology, successfully tested in real-time fire tests.

Technical Specifications

External Dimensions (LxWxH cm)	60 x 40 x 28
Internal Dimensions (LxWxH cm)	52 x 32 x 24.5
Stack Height (cm)	28
Tare Weight (kg)	8
Volume (litres)	41
Maximum Payload (kg)	14 (including extinguishing beads)
Max Battery Power (watts)	800
Cable Entry Gland	Included
Extinguishing Beads	Included
Pressure Relief	2 no. Top Filtered Vents
Handling	1 no. Front Handle
Casing Material	Polypropylene

Key Advantages

- Non-inflammable Inner Housing
- Light Weight
- Easy Handling
- Explosion Protection
- Pressure Relief Vents
- Filtered Ventilation
- For Indoor and Outdoor Use
- Eco-friendly Extinguishing Agent
- UN Certified
- Easy Carry Handle
- Charging Cable Entry Included
- Robust Outer Casing

How to Use

1 Insert one pouch of the extinguishing agent

2 Place the battery in the center of the case

3 Fill all free space with extinguishing agent and close the cover

4 Close the latch and push down locking tab

Charging Cable

1

2

3

4